MICROBATTERY.COM

7350 NW 35th Terrace, Miami, Florida 33122 Customer Service: 1-866-999-2355 Phone: 1-305-371-9200 Fax: 1-305-371-9400

www.microbattery.com

ENERGIZER 10 size - Mercury Free






(top view) (bottom view)

Industry Standard Dimensions

mm (inches)



Typical Discharge Characteristics

ANSI/IEC Industry Standards / Intermittent Test Protocol (3K ohm 12 hours per day at 21C)



Specifications

Chemical System: Zinc Air (Zn/O₂)

Yellow Tab Color:

Designation: ANSI-7005ZD, IEC-PR70

1.4 Volts Nominal Voltage:

Typical Capacity: 91 mAh (to 0.9 volts)

(Rated at 3k ohms at 21°C/50% RH)

Typical Weight: 0.32 grams (0.01 oz.)

0.08 cubic centimeters (0.005 cubic inch) Typical Volume:

Typical Discharge Characteristics

IEC Industry Standards / Standard Test Protocol (3/.7 mA .1S/1H59M 59.9S 12H at 21C)



Typical Discharge Characteristics

IEC Industry Standards / High Drain Test Protocol (5/1 mA .1S/1H59M 59.9S 12H at 21C)



Important Notice

This data sheet contains typical information specific to products manufactured at the time of its publication. ©Energizer Holdings, Inc. - Contents herein do not constitute a warranty.

Form No. EBC - 4507I Page 1 of 1