MICROBATTERY.COM

7350 NW 35th Terrace, Miami, Florida 33122 Customer Service: 1-866-999-2355 Phone: 1-305-371-9200 Fax: 1-305-371-9400

www.microbattery.com

ENERGIZER 13 size - Mercury Free






(top view) (bottom view)

Industry Standard Dimensions

mm (inches)



Typical Discharge Characteristics

IEC Industry Standards / Standard Test Protocol (6/2 mA .1S/1H59M 59.9S 12H at 21C)

Specifications

ANSI-7000ZD, IEC-PR48

280 mAh (to 0.9 volts)

0.8 grams (0.03 oz.)

(Rated at 1.5k ohms at 21°C/50% RH)

0.03 cubic centimeters (0.02 cubic inch)

Zinc Air (Zn/O₂)

Orange

1.4 Volts

Chemical System:

Nominal Voltage:

Typical Capacity:

Typical Weight:

Typical Volume:

Tab Color:

Designation:



Typical Discharge Characteristics

ANSI/IEC Industry Standards / Intermittent Test Protocol (1.5K ohm 12 hours per day at 21C)



Typical Discharge Characteristics

IEC Industry Standards / High Drain Test Protocol (12/3 mA .1S/1H59M 59.9S 12H at 21C)



Important Notice

This data sheet contains typical information specific to products manufactured at the time of its publication. ©Energizer Holdings, Inc. - Contents herein do not constitute a warranty.

Form No. EBC - 4503H Page 1 of 1